MAXXUM ROPS









The Case IH Maxxum ROPS is available in two sizes; the four cylinder 110 and the six cylinder 125.

These popular tractors combine the great features & strength of the legendary Case IH Maxxum with the ease of access of a ROPS tractor. Maxxum ROPS is ideal for dairy operations in our region. The Maxxum is also available with a cab and is one of our most popular tractors.

MAXXUM 110 ROPS SPECIFICATIONS

Engine		FPT NEF 4.5 litre, 4 cyl, turbo, mechanical injection, Tier 3
Rated power @ 2200 rpm	ECE R120	107 hp
Max Torque @ 1,250 rpm		455 Nm
Fuel Tank		176 litres* with guard
Transimission		40km/h 16x16 semi powershift, power-synchro shuttle
Front Axle		Class 3, 4WD, limited slip diff, 55° Steering angle
Rear Axle	330331	HD Flange with diff lock, IAR 1:1.353
Brakes		Extended life multi-disc in rear axle
Hydraulics	334844	64 l/min fixed display, pump with 3 mech, rear remotes
Linkage	330970	MDC, max capacity: 5,682kg, 1 int. + 2 external rams Cat 2 hook ends
PTO PTO	330801	540, 540E & 1000 with 6 x 21 spline shafts
Electric System		12v, 120 amp alternator, 1x 107ah battery
Cab		ROPS with canopy, RH and LH steps, mirrors
Work lights	330925	2 rear on ROPS frame
Frame	330217	Narrow rear fenders, dynamic front fenders
Ballast		Front weight carrier with 6 weight pack
Wheelbase		2,412 mm*
Minimum shipping weight		4,500 kg*
Wheels		540/65/R38 & 440/65/R28

MAXXUM 125 ROPS SPECIFICATIONS

Engine		FPT NEF 6.7 litre, 6 cyl, turbo, Mmechanical injection, Tier 3
Rated power @ 2200 rpm	ECE R120	126 hp
Max Torque @ 1,250 rpm		560 Nm
Fuel Tank		250 litres with guard
Transimission		40km/h 16x16 semi powershift, power-synchro shuttle
Front Axle		Class 3, 4WD, limited slip diff, 55° Steering angle
Rear Axle		Flange axle with diff lock, IAR 1:1.353
Hydraulics	334844	113 l/min with CCLS with 3 mech, rear remotes (2 configurable)
Linkage	330970	MHC, max capacity: 5,628kg, with Cat 2 hook ends
PTO	330801	540, 540E & 1000 with 6 x 21 spline shafts
Electric System		12v, 120 amp alternator, 1x 107ah battery
Cab		ROPS with canopy, RH and LH steps, mirrors
Work lights	330925	2 rear on ROPS frame
Frame	330217	Narrow rear fenders, dynamic front fenders
Ballast		Wide front weight carrier — no weights
Wheelbase		2,652 mm
Minimum shipping weight		Approx 4,700 kg
Wheels		650/60/R38 &520/60/R28 or 600/65/R38 & 480/65/R28
		* approximate size



3 Year/3000 Hour Warranty

We recognise you expect your product will deliver on the ever increasing productivity demands. Case IH customers deserve the additional peace of mind of knowing your product is covered should the unexpected occur with 3 years/ 3000 hour standard REDCover Plus Protection Plan.

